

ASSEMBLY INSTRUCTIONS FOR 5' OCTAGONAL PICNIC TABLE WITH ATTACHED SEATS--T50A (T50A-SCR SCREW PACK)

1. Prepare a level area for the table. Position the base assembly with the center notches facing up in the level area. Then set the base assembly with the center notches facing down over the first base assembly (the notches should fit together). The two base assemblies should be at right angles to each other.
2. Hold the two sets of 2x6's from the base assemblies apart as needed so each 2x6 is against the outside of the notches on the other 2x6's. Use four 3" screws driven through the predrilled holes in the top 2x6's to fasten the two bases to each other. Check that the 2x6's remained spread apart so an umbrella pipe can fit between them
3. Lay the tabletop over the base. Position the top and the base so the upright 2x6 on each base corner fits into the gap in the 2x cleats underneath the tabletop.
4. Attach the top to the base by driving a 2 1/2" screw through the predrilled hole in the outside corners of each cleat into the upright 2x6.

MAINTENANCE AND USE INSTRUCTIONS

1. Check that screws are still tight three weeks after the table has been assembled. Check regularly and tighten or replace screws as necessary thereafter.
2. Inspect the table regularly. Splintered surfaces should be sanded smoothly to avoid danger of injury.