ASSEMBLY INSTRUCTIONS FOR 3X8 TABLE W/ATTACHED SEATS (T38A HARDWARE PACK)

CAUTION: At least two adults should work together to set up this table.

1. Identify the ten main pieces: one table top, two table seats, three table leg assemblies, four braces, and hardware pack.

2. Place table top face down on a flat smooth surface (we recommend using the box that the top was shipped in for a clean and smooth surface).

3. Position the narrow end of one leg assembly outside the 1 3/8"x 2 ½" cross piece that is fastened to the table top. Fasten the leg frame by driving one ¼" x 2 ½" washer head lag through each pre drilled hole (in the cross piece) and into the leg frame.

4. Attach the other end leg brace assembly to the table top in the same way the first one was fastened.

5. Attach the center leg assembly so that the legs line up with the bench cleats and fasten the same way as the other two leg frames.

6. Turn the table right side up.

7. Take one table seat and position it on top of the seat supports. If the leg frames were positioned correctly the seat cleats will go right beside the seat supports. Allow the table seat to extend beyond the seat support approximately ¼". Fasten seat support to leg assembly with 2 ½" screws through the seat cleat into the seat support.

8. Attach the second seat to the leg assembly the same way the first one was fastened.

9. Turn the table upside down to fasten braces.

10. Position one of the braces so that it is near the center of the 2x6 cross piece on the leg assembly and near the center of the table top, placing it off center enough to avoid the space between the table top boards. The brace should lay nicely against the table top and leg assembly Fasten with 2 ½" washer head lags.

l l. Attach the rest of the braces following the same logic as the first brace. The center leg support will have two braces fastened to it.

10. Turn the table upright and enjoy

MAINTENANCE AND USE INSTRUCTIONS

1. Tighten all lags and screws three weeks after table is assembled. Check regularly and tighten as necessary thereafter.

2. Inspect regularly for broken or damaged pieces. Splintered surfaces should be sanded smooth to avoid danger of injury. Cracks resulting from weathering are normal; pieces developing those cracks do not need to be replaced. Pieces with structural cracks do need to be replaced promptly, however.